

STRING COURSE OF PAVERS  
AROUND COLLAR

REBAR

CONCRETE COLLAR

GRATE AND FRAME

CONCRETE PAVER  
3 1/8" (80 MM)

1" (25 MM)  
BEDDING SAND

BASE MATERIAL

GEOTEXTILE

1" (25 MM) DIA.  
WEEP HOLES  
ONE PER SIDE

GRATE AND FRAME

CONCRETE COLLAR  
MIN 8" (200 MM) WIDE  
ELEVATION TO BE  
1/4" (7 MM) BELOW PAVERS

REBAR

12" (300 MM) WIDE GEOTEXTILE  
TURN UP AGAINST COLLAR


COMPACTED SOIL SUBGRADE

CONCRETE CATCH BASIN  
PER LOCAL STANDARD

**SECTION AA**

**NOTES:**

1. SIZE AND REINFORCING OF CONC. VARIES WITH TRAFFIC.
2. INSERT 1 IN. DIA. (25 MM) WEEP HOLES, ONE PER SIDE, BOTTOM OF WEEPHOLE TO BE LEVEL WITH SURFACE OF BASE. COVER WITH GEOTEXTILE.



**CATCH BASIN**

DRAWING NO.

ICPI-26

SCALE

F.S.